

100 SERIES CASEMENT WINDOWS

Table of Sizes – Picture Window With Flanking Casements

Scale 1/8" (3) = 1'-0" (305) – 1:96

Window Dimension	5'-11 1/2" (1816)	7'-11 1/2" (2426)	9'-11 1/2" (3035)	11'-11 1/2" (3645)
Minimum Rough Opening	6'-0" (1829)	8'-0" (2438)	10'-0" (3048)	12'-0" (3658)
Unobstructed Glass (width of center sash)	29 1/4" (743)	41 1/4" (1048)	53 1/4" (1353)	65 1/4" (1657)
Unobstructed Glass (width of single flanking sash)	11 1/4" (286)	17 1/4" (438)	23 1/4" (591)	29 1/4" (743)
11'-1/2" (292)	16-3010-16	20-4010-20	26-5010-26	30-6010-30
1'-5 1/2" (445)	16-3016-16	20-4016-20	26-5016-26	30-6016-30
1'-11 1/2" (597)	16-3020-16	20-4020-20	26-5020-26	30-6020-30
1'-11 1/2" (597)	16-3020-16	20-4020-20	26-5020-26	30-6020-30
2'-5 1/2" (749)	16-3026-16	20-4026-20	26-5026-26	30-6026-30
2'-11 1/2" (902)	16-3030-16	20-4030-20	26-5030-26	30-6030-30
3'-5 1/2" (1054)	16-3036-16	20-4036-20	26-5036-26	30-6036-30 ^Ø
3'-11 1/2" (1207)	16-3040-16	20-4040-20	26-5040-26 ^Ø	30-6040-30 ^Ø
4'-5 1/2" (1359)	16-3046-16	20-4046-20	26-5046-26 ^Ø	30-6046-30 ^Ø
4'-11 1/2" (1511)	16-3050-16	20-4050-20	26-5050-26 ^Ø	30-6050-30 ^Ø
5'-5 1/2" (1664)	16-3056-16	20-4056-20	26-5056-26 ^Ø	30-6056-30 ^Ø
5'-11 1/2" (1816)	16-3060-16	20-4060-20	26-5060-26 ^Ø	30-6060-30 ^Ø

Choose left, right or stationary as viewed from the exterior. In addition to venting shown, other standard configurations are available. Windows have one continuous outer frame.

Transoms are also shown.

* "Window Dimension" always refers to outside frame-to-frame dimension.

* "Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.

* Dimensions in parentheses are in millimeters.

Ø Meets or exceeds clear opening area of 5.7 sq. ft. or 0.53 m², clear opening width of 20" (508) and clear opening height of 24" (610).