

100 SERIES SINGLE-HUNG WINDOWS

Table of Arch Single-Hung Window Sizes

Scale 1/8" (3) = 1'-0" (305) – 1:96

Window Width Dimension		1'-11 1/2"	2'-5 1/2"	2'-11 1/2"	3'-5 1/2"
		(597)	(749)	(902)	(1054)
Minimum Rough Opening		2'-0"	2'-6"	3'-0"	3'-6"
		(610)	(762)	(914)	(1067)
Unobstructed Glass (width of upper sash)		20"	26"	32"	38"
		(508)	(660)	(813)	(965)
Unobstructed Glass (width of lower sash)		17 1/4"	23 1/4"	29 1/4"	35 1/4"
		(438)	(591)	(743)	(895)
Radius		23 1/2" (597)	29 1/2" (749)	35 1/2" (902)	41 1/2" (1054)
Chord Height		3 1/8" (79)	4" (102)	4 3/4" (121)	5 1/2" (140)
Unobstructed Glass (height of lower sash shown below)		10 9/16" (268)	15 1/16" (383)	16 11/16" (424)	17 1/2" (445)
Side Height		2'-5 1/2" (749)	2'-9 1/2" (851)	2'-10 1/4" (870)	2'-11" (889)
Window Height (shown left of window)		2'-8 5/8" (829)	2'-9 1/2" (851)	2'-10 1/4" (870)	2'-11" (889)
Minimum Rough Opening = Window Height + 1/2" (13)		2'-9 1/8" (832)	2'-10 1/8" (854)	2'-10 5/8" (873)	2'-11 1/2" (892)
		2026	2626	3026	3626
		13 9/16" (345)	18 1/16" (459)	19 11/16" (500)	20 1/2" (521)
		2'-11 1/2" (902)	3'-3 1/2" (1003)	3'-4 1/4" (1022)	3'-5" (1041)
		2030	2630	3030	3630
		16 9/16" (421)	21 1/16" (535)	22 11/16" (576)	23 1/2" (597)
		3'-5 1/2" (1054)	3'-9 1/2" (1156)	3'-10 1/4" (1175)	3'-11" (1194)
		2036	2636	3036	3636
		19 9/16" (497)	24 1/16" (611)	25 11/16" (652)	26 1/2" (673)
		3'-11 1/2" (1207)	4'-3 1/2" (1308)	4'-4 1/4" (1327)	4'-5" (1346)
		2040	2640	3040	3640
		22 9/16" (573)	27 1/16" (687)	28 11/16" (729)	29 1/2" (749)
		4'-5 1/2" (1359)	4'-9 1/2" (1461)	4'-10 1/4" (1480)	4'-11" (1499)
		2046	2646	3046	3646
		25 9/16" (649)	30 1/16" (764)	31 11/16" (805)	32 1/2" (826)
		4'-11 1/2" (1511)	5'-2 5/8" (1591)	5'-4 1/4" (1632)	5'-5" (1651)
		2050	2650	3050 ^o	3650 ^o
		28 9/16" (726)	33 1/16" (840)	34 11/16" (881)	35 1/2" (902)
		5'-5 1/2" (1664)	5'-9 1/2" (1765)	5'-10 1/4" (1784)	5'-11" (1803)
		2056	2656	3056 ^o	3656 ^o
		31 9/16" (802)	36 1/16" (916)	37 11/16" (957)	38 1/2" (978)
		5'-11 1/2" (1816)	6'-2 5/8" (1895)	6'-4 1/4" (1937)	6'-5" (1956)
		2060	2660 ^o	3060 ^o	3660 ^o
		34 9/16" (878)	39 1/16" (992)	40 11/16" (1033)	41 1/2" (1054)
		6'-5 1/2" (1969)	6'-8 5/8" (2048)	6'-10 1/4" (2089)	6'-11" (2108)
		2066	2666 ^o	3066 ^o	3666 ^o

continued on next page

* "Window Dimension" always refers to outside frame-to-frame dimension.

* "Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.

* Dimensions in parentheses are in millimeters.

* Meets or exceeds clear opening area of 5.7 sq. ft. or 0.53 m², clear opening width of 20" (508) and clear opening height of 24" (610).

* For side heights greater than 6'-5 1/2" (1969), meeting rail location = (side height in inches x 0.33) + 1.96".



Custom-size windows


are available in 1/8" (3)

increments. Contact your

Andersen supplier for more information.

For arch single-hung windows, the size designation does not reflect the overall window height (e.g., a 2026 window size has a side height of 2'-5 1/2" and an overall window height of 2'-8 5/8").

Height dimensions for upper sash are to the right of each window size and lower sash are to the far left.



Windows with a side height greater than 6'-5 1/2" (1969) are only available with a 2:1 reverse cottage sash ratio.*

Table of Arch Single-Hung Window Sizes (continued)

Scale $\frac{1}{8}"$ (3) = 1'-0" (305) – 1:96

[illegible]

Custom-size windows

are available in 1/8" (3)

increments. Contact your

Andersen supplier for more information.

For arch single-hung windows, the size designation does not reflect the overall window height (e.g., a 2026 window size has a side height of 2'-5 1/2" and an overall window height of 2'-8 5/8").

Height dimensions for upper sash are to the right of each window size and lower sash are to the far left.



Windows with a side height greater than 6'-5 1/2" (1969) are only available with a 2:1 reverse cottage sash ratio.*

- “Window Dimension” always refers to outside frame-to-frame dimension.

- **“Minimum Rough Opening”** dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.

- Dimensions in parentheses are in millimeters.

◆Meets or exceed clear opening area of 5.7 sq. ft. or 0.53 m², clear opening width of 20" (508) and clear opening height of 24" (610).

*For side heights greater than 6'-5 1/2" (1969), meeting rail location = (side height in inches x 0.33) + 1.96".